

Stewart

Filmscreen Corporation®

P i c t u r e P e r f e c t



Luxus "Model A" ElectriScreen

Stylish and Professional

Luxus "Model A" ElectriScreen's design is ideal for video production and for multi-purpose use, including film and graphic presentations.

Motorized Roller System

Stewart's motorized roller system provides a quiet, reliable screen operation that can be activated by a switch, infrared or remote control, or a projector screen trigger.

Insist on the Best

Optimize your "Model A" ElectriScreen with a Stewart Academy Award® winning screen material, securely attached using our exclusive Tab-Guy tensioning system designed to ensure a smooth flat image and prevent edge curl.

Hidden from View


The screen's motorized housing may be placed above the ceiling, with the screen descending through a small slot, wall mount or concealed behind a decorator fascia or cornice that blends with the room's décor.

Trust Stewart

Stewart Filmscreen is synonymous with high quality materials, superior craftsmanship and long, trouble-free product life. Since every Stewart Filmscreen product is hand crafted, custom sizes and configurations can also be accommodated. Call Stewart Filmscreen today and we will build one for you.

Luxus "Model A" ElectriScreen Specifications

Dimensions represented in inches (") and millimeters (mm). Weights represented in pounds (lbs.) and kilograms (kg.)



Luxus Model A


Formats	Min-Max Height	Min-Max Width
AV	50"-70"	50"-70"
Video	36"-72"	48"-96"
HDTV	40.5"-60"	72"-107"
Widescreen	39"-60"	72"-111"



Luxus Model A

Luxus Model A Classic

Formats	Min-Max Height	Min-Max Width
AV	84"	84"
Video Format	90"-108"	120"-144"
HDTV	66"	118"
Widescreen	66"	122"



Luxus Model A Classic

(Size height and width depends on model chosen.
Custom sizes available with no extra charge.)

Specifications

Case Material	Aluminum Extrusion
Case Color	Black, Gray, White
Batten Colors	Black, White

Screen Materials

Front Projection	Gain	Viewing Angle
GrayHawk RS	.92	128°
Studiotek / Ultramatte 130	1.3	160°
FireHawk	1.35	100°
Ultramatte 150	1.5	140°
Videomatte 200	1.8	120°
Ultramatte 200	2.0	120°

Perforation (Front Projection)		
THX Certified MicroPerf		Optional
CinePerf		Optional

Rear Projection	Gain	Viewing Angle
Aeroview 100	1.0	180°
Filmscreen 100	1.0	100°-120°
Lumiflex 130	1.3	160°
Filmscreen 150	1.5	120°

Control Systems : Screen

High Voltage Wall Switch	Included
Low Voltage Control	Optional
Wireless Remote Control	Optional
Infrared Remote Control	Optional
Screen Trigger Interface	Optional
Video Interface Control	Optional

Mounting Hardware

Wall Mount/Brackets	Included
Ceiling Mount	Optional
Hanging (Eyebolts)	Optional

For custom sizes and gains, please consult the Screen Assistant software or Stewart Sales desk.

Video Format (4:3 Aspect Ratio)

Model Number	Image Diagonal	Image Height	Image Width
LX060V	60" (1524mm)	36 (914)	48 (1219)
LX072V	72 (1829)	43 (1092)	57 (1448)
LX084V	84 (2134)	50 (1270)	67 (1702)
LX090V	90 (2286)	54 (1372)	72 (1829)
LX100V	100 (2540)	60 (1524)	80 (2032)
LX120V	120 (3048)	72 (1829)	96 (2438)
*LXC150V	150 (3810)	90 (2286)	120 (3048)
*LXC180V	180 (4572)	108 (2743)	144 (3658)

HDTV Format (16:9 Aspect Ratio)

Model Number	Image Diagonal	Image Height	Image Width
LX082H	82 (2083)	40.5 (1029)	72 (1829)
LX092H	92 (2337)	45 (1143)	80 (2032)
LX100H	100 (2540)	49 (1245)	87 (2210)
LX110H	110 (2794)	54 (1372)	96 (2438)
LX123H	123 (3124)	60 (1524)	107 (2718)
*LXC135H	135 (3429)	66 (1676)	118 (2997)

Standard Case: Height 5.25" (133mm) Depth 5.5" (140)
***Classic Case:** Height 8" (203) Depth 6" (152)

Sizes and specifications are subject to change at anytime.