

Stewart

Filmscreen Corporation®
P i c t u r e P e r f e c t



Visionary ElectriScreen

Simplicity

Stewart Filmscreen's Visionary ElectriScreen is the most innovative and installation friendly screen available. Designed for new construction or installations where the screen needs to be retro-fitted, the case is available to ship in advance to help speed up the construction process.

Motorized Roller System

Stewart's motorized roller system provides a quiet, reliable screen operation that can be activated by a switch, infrared or remote control, or a projector screen trigger.

Hidden from View

The Visionary features a self-finishing, seamless bottom plate, factory preset drywall and plaster flange stops to accommodate various ceiling configurations. An ideal choice where the screen needs to disappear when not in use.

Insist on the Best


Optimize your Visionary ElectriScreen with a Stewart Academy Award® winning screen material, securely attached using our exclusive Tab-Guy tensioning system designed to ensure a smooth flat image and prevent edge curl.

Trust Stewart

Stewart Filmscreen is synonymous with high quality materials, superior craftsmanship and long, trouble-free product life. Since every Stewart Filmscreen product is hand crafted, custom sizes and configurations can also be accommodated. Call Stewart Filmscreen today and we will build one for you.

Visionary ElectriScreen Specifications

Dimensions represented in inches (") and millimeters (mm). Weights represented in pounds (lbs.) and kilograms (kg.)



Formats	Min-Max Height	Min-Max Width
Video Format	36"-90"	48"-120"
HDTV	40.5"-66"	72"-118"
Widescreen	39"-66"	72"-122"

(Size height and width depends on model chosen.
Custom sizes available with no extra charge.)

Specifications

Case Material	Aluminum Extrusion
Case Color	White
Batten Colors	Black, White

Screen Materials

Front Projection	Gain	Viewing Angle
GrayHawk RS	.92	128°
Studiotek / Ultramatte 130	1.3	160°
FireHawk	1.35	100°
Ultramatte 150	1.5	140°
Videomatte 200	1.8	120°
Ultramatte 200	2.0	120°

Perforation (Front Projection)

THX Certified MicroPerf	Optional
CinePerf	Optional

Rear Projection	Gain	Viewing Angle
Aeroview 100	1.0	180°
Filmscreen 100	1.0	100°-120°
Lumiflex 130	1.3	160°
Filmscreen 150	1.5	120°

Standard Features

- Tab-Guy Tensioning System
- Roller Tube System
- Seamless Screen Materials
- Screen Motor: 120 Volt = 38 rpm, 1 amp
220 Volt = 32 rpm, 1 amp
- Sonic Insulated Screen Drive
- Case and Screen may ship separately as needed

Control Systems : Screen

High Voltage Wall Switch	Included
Low Voltage Control	Optional
Wireless Remote Control	Optional
Infrared Remote Control	Optional
Video Interface Control	Optional

Mounting Hardware

Ceiling/Soffit Recessed	Included
-------------------------	----------

Video Format (4:3 Aspect Ratio)

Model Number	Image Diagonal	Image Height	Image Width
VE060V	60" (1524mm)	36 (914)	48 (1219)
VE072V	72 (1829)	43 (1092)	57 (1448)
VE084V	84 (2134)	50 (1270)	67 (1702)
VE090V	90 (2286)	54 (1372)	72 (1829)
VE100V	100 (2540)	60 (1524)	80 (2032)
VE120V	120 (3048)	72 (1829)	96 (2438)
VE150V	150 (3810)	90 (2286)	120 (3048)

HDTV Format (16:9 Aspect Ratio)

Model Number	Image Diagonal	Image Height	Image Width
VE082H	82 (2083)	40.5 (1029)	72 (1829)
VE092H	92 (2337)	45 (1143)	80 (2032)
VE100H	100 (2540)	49 (1245)	87 (2210)
VE110H	110 (2794)	54 (1372)	96 (2438)
VE123H	123 (3124)	60 (1524)	107 (2718)

Standard Case: Height 6.69" (170mm) Depth 7.87" (200)

Sizes and specifications are subject to change at anytime.

For custom sizes and gains, please consult the Screen Assistant software or Stewart Sales desk.